

## 8030 Slim Series

RoHS COMPLIANT ✓ CE F

## 15W Polo Circular Led Bulkhead

- High Light Transmittance PC Diffuser
- Anti UV and Fire self-extinguishing Material
- 28Watt CFL Replacement
- Up to 50% Energy Cost Savings
- No UV/IR radiation

- No Visual LEDs
- 50000 Switching Times
- Waterproof Rate: IP54/65
- Epistar(SMD2835) & Samsung(SMD5630) Chips
- 2 year guarantee



LED

### Specifications

Input: 220-240V 50-60Hz 0.068Amp

Output: 360mA 36V Max.15W / 300mA 6.4V Max.2W (FOR EMERGENCY)

Power Factor: >0.85 Efficacy: 85% CRI>80 Color Temperature: 3500K/4000K/6000K

Product Size: 32(D) \* 10(M) cm

### Normal/Microwave Sensor/Emergency/MS-Emergency

Code	Power	LED Chip	Chip Qty	Lumen(lm)	Inner Box	Outer Carton
8030-15W	15W	SMD2835	72	1400	1	10
8030-15W-MS	15W	SMD2835	72	1400	1	10
8030-15W-EKT	15W/2W	SMD2835/5630	72/4	1400/200	1	10
8030-15W-MSEKT	15W/2W	SMD2835/5630	72/4	1400/200	1	10

## 0401, 0501 Series

RoHS COMPLIANT ✓ CE F

LED

## LED Moisture-proof Light

### Feature

- PC shell, PC cover, high light transmittance, durable
- Can be installed with a microwave sensor
- Energy saving: replace general halogen light directly, saving more than 80% energy
- Environmentally friendly: no heat, UV or infrared in the beam; no mercury
- IP54 Surface protection, suitable for commercial lighting and architectural lighting

Voltage: AC100-277V AC185-265V PF>0.5&PF>0.7 50/60Hz

Color temperature: 2800-3100K 3800-4250K 5000-5300K 6000-6500K



0401-8W



0401-12W



0501-8W



0501-12W

Model	Parameter	Size(LxWxH)
0401-8W	640LM RA80	φ 176x55mm
0401-12W	860LM RA80	φ 211x55mm
0401-16W	1280LM RA80	φ 211x55mm
0401-18W	1440LM RA80	φ 211x55mm
0501-8W	640LM RA80	200x100x55mm
0501-12W	860LM RA80	230x105x55mm
0501-16W	1280LM RA80	230x105x55mm
0501-18W	1440LM RA80	230x105x55mm

## 0601, 0701 Series

RoHS COMPLIANT ✓ CE F

LED

## LED Moisture-proof Light

### >> Feature

- ABS shell, PC cover, high light transmittance, durable
- Can be installed with a microwave sensor
- Energy saving: replace general halogen light directly, saving more than 80% energy
- Environmentally friendly: no heat, UV or infrared in the beam; no mercury
- IP54 Surface protection, suitable for commercial lighting and architectural lighting

Voltage: AC100-240V AC185-265V PF>0.5&PF>0.7 50/60Hz  
Color temperature: 2800-3100K 3800-4250K 5000-5300K 6000-6500K



0701-15W



0601-8W



Model	Parameter	Size(LxWxH)
0601-8W	800LM RA80	φ 175x45mm
0701-15W	1400LM RA80	175x70x45mm

### WenZhou Laman Electric Co.,Ltd

Add: No 52 of West Garden Road, HeBei Industrial Park,  
PanShi Town 325602, Wenzhou, P.R.China

Tel: 0086-577-62830722

Fax: 0086-577-62830227

E-mail: [lamanelectric.com](mailto:lamanelectric.com)

Web: [www.lamanelectric.com](http://www.lamanelectric.com)

